

TECHNICAL DATA

TAMPER

BT 60 E



Greater ease of operation

Comfort start at the push of a button,
low hand-arm vibrations



Performance without compromise

Optimum compaction power and
stable running properties



Low service costs

Maintenance-free electric motor and
full engine protection

Shipping dimensions in m3


BT 60 E 0,262

Standard Equipment

- Comfort start
- Maintenance-free brushless electric motor
- Protective engine covering
- Tool-free battery swap
- Vibration insulated steering handle
- Single point lifting device
- Protective covering
- Plastic castor as loading aid
- 3-2-1 Warranty

Optional Equipment

- Battery eP 20 (20Ah)
- Battery eP 28 (28Ah)
- Standard charger
- Quick charger
- Transport device with puncture proof wheels
- Tamper foot widths (160-280mm)
- Special painting
- Tool kit



Dimensions in mm

	B	H	L	L1	W
BT 60 E	350	1030	728	335	230

Technical Data

**BOMAG
BT 60 E**

Weights

Operating weight CECE	kg	71
Basic weight	kg	61

Dimensions

Working width (tamper plate)	mm	230
------------------------------------	----	-----

Driving Characteristics

Working speed max.	m/min	20
Area coverage max.	m ² /h	276

Drive

Type		Asynchronomotor
Cooling		air
Performance	kW	2,3
Speed	min ⁻¹	4.200
Drive system		mech.

Exciter system

Frequency	Hz	11,6
Impact force	kN	15,0
Jumping height	mm	70,0

Electric equipment

Operating voltage	V	51
battery, type		Li-Ion

Technical modifications reserved. Machines may be shown with options.



PRE 541 45 010

300921 Sa

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

