

HELIXX(TM) Poly Hoppers Specifications

Construction

Imperial	11780	11790	11800	11810
Frame	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Hopper	One-piece LLDPE safety	One-piece LLDPE safety	One-piece LLDPE safety	One-piece LLDPE safety
	yellow poly with integral			
	vertical rib construction	vertical rib construction	vertical rib construction	vertical rib construction
Motors	Dual, 12-volt DC motor			
	mounted in weather	mounted in weather	mounted in weather	mounted in weather
	resistant enclosure	resistant enclosure	resistant enclosure	resistant enclosure
Spinner Drive Assembly	Flip Up/Removable	Flip Up/Removable	Flip Up/Removable	Flip Up/Removable
	Chute	Chute	Chute	Chute
Spinner	12" heavy-duty	12" heavy-duty	12" heavy-duty	12" heavy-duty
	polyurethane spinner	polyurethane spinner	polyurethane spinner	polyurethane spinner
	with integral hub	with integral hub	with integral hub	with integral hub
	assembly	assembly	assembly	assembly
HELIXX Drive Assembly	Heavy-duty solid steel	Heavy-duty solid steel	Heavy-duty solid steel	Heavy-duty solid steel
	construction with	construction with	construction with	construction with
	maximum-torque motor	maximum-torque motor	maximum-torque motor	maximum-torque motor
	transmission drive	transmission drive	transmission drive	transmission drive
HELIXX	6.25" heavy-duty	6.25" heavy-duty	6.25" heavy-duty	6.25" heavy-duty
	shaftless auger variable	shaftless auger variable	shaftless auger variable	shaftless auger variable
	pitch steel flighting	pitch steel flighting	pitch steel flighting	pitch steel flighting
Mounting	Truck bed mounted with			
	ratchet-strap assist	ratchet-strap assist	ratchet-strap assist	ratchet-strap assist

Metric	11780	11790	11800	11810
Frame	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Hopper	One-piece LLDPE safety	One-piece LLDPE safety	One-piece LLDPE safety	One-piece LLDPE safety
	yellow poly with integral			
	vertical rib construction	vertical rib construction	vertical rib construction	vertical rib construction
Motors	Dual, 12-volt DC motor			
	mounted in weather	mounted in weather	mounted in weather	mounted in weather
	resistant enclosure	resistant enclosure	resistant enclosure	resistant enclosure
Spinner Drive Assembly	Flip Up/Removable	Flip Up/Removable	Flip Up/Removable	Flip Up/Removable
	Chute	Chute	Chute	Chute
Spinner	30.5 cm heavy-duty	30.5 cm heavy-duty	30.5 cm heavy-duty	30.5 cm heavy-duty
	polyurethane spinner	polyurethane spinner	polyurethane spinner	polyurethane spinner
	with integral hub	with integral hub	with integral hub	with integral hub
	assembly	assembly	assembly	assembly
HELIXX Drive Assembly	Heavy-duty solid steel	Heavy-duty solid steel	Heavy-duty solid steel	Heavy-duty solid steel
	construction with	construction with	construction with	construction with
	maximum-torque motor	maximum-torque motor	maximum-torque motor	maximum-torque motor
	transmission drive	transmission drive	transmission drive	transmission drive
HELIXX	15.9 cm heavy-duty	15.9 cm heavy-duty	15.9 cm heavy-duty	15.9 cm heavy-duty
	shaftless auger variable	shaftless auger variable	shaftless auger variable	shaftless auger variable
	pitch steel flighting	pitch steel flighting	pitch steel flighting	pitch steel flighting



HELIXX(TM) Poly Hoppers Specifications

Mounting	Truck bed mounted with			
	ratchet-strap assist	ratchet-strap assist	ratchet-strap assist	ratchet-strap assist

Dimensions

Imperial	11780	11790	11800	11810
Approx. Weight (Empty)	412 lb	443 lb	694 lb	718 lb
Overall Length	106"	115"	133"	133"
Overall Height	52"	59"	76"	83.5"
Overall Width	49"	49"	67.25"	67.25"
Min. Bed Length	72"	80"	98"	98"
Hopper Length	80.75"	89.75"	109"	109"
Hopper Height	34.5"	41.5"	46.5"	54"
Hopper Width	49"	49"	67.25"	67.25"

Metric	11780	11790	11800	11810
Approx. Weight (Empty)	186.9 kg	200.9 kg	315.2 kg	325.7 kg
Overall Length	269.2 cm	292.1 cm	287.0 cm	287.0 cm
Overall Height	132.1 cm	149.9 cm	193.0 cm	212.1 cm
Overall Width	124.46 cm	124.46 cm	170.82 cm	170.82 cm
Min. Bed Length	182.88 cm	203.2 cm	248.92 cm	248.92 cm
Hopper Length	205.1 cm	227.9 cm	276.86 cm	276.86 cm
Hopper Height	87.63 cm	105.41 cm	118.11 cm	137.16 cm
Hopper Width	124.46 cm	124.46 cm	170.82 cm	170.82 cm

Electrical

Imperial	11780	11790	11800	11810
Speed Control	Digital, self-diagnosing	Digital, self-diagnosing	Digital, self-diagnosing	Digital, self-diagnosing
	dual variable-speed	dual variable-speed	dual variable-speed	dual variable-speed
	control with auto reverse			
Wiring Harness	Single, 4-pin control	Single, 4-pin control	Single, 4-pin control	Single, 4-pin control
	harness wire to enter cab			

Metric	11780	11790	11800	11810
Speed Control	Digital, self-diagnosing	Digital, self-diagnosing	Digital, self-diagnosing	Digital, self-diagnosing
	dual variable-speed	dual variable-speed	dual variable-speed	dual variable-speed
	control with auto reverse			
Wiring Harness	Single, 4-pin control	Single, 4-pin control	Single, 4-pin control	Single, 4-pin control
	harness wire to enter cab			

Operational

Imperial	11780	11790	11800	11810
Capacity (Volume)	1.5 cu yd	2.25 cu yd	3.5 cu yd	5.0 cu yd
Capacity (Weight)	3,120 lb	4,680 lb	7,280 lb	10,400 lb



HELIXX(TM) Poly Hoppers Specifications

Spreading Width 8 - 40 ft				
---------------------------	-----------	-----------	-----------	--

Metric	11780	11790	11800	11810
Capacity (Volume)	1.1 cu m	1.7 cu m	2.7 cu m	3.8 cu m
Capacity (Weight)	1,415.2 kg	2,122.8 kg	3,302.3 kg	4,717.4 kg
Spreading Width	2.4 - 12.2 m			

Standard Equipment

Imperial	11780	11790	11800	11810
Top Screen	Heavy-duty steel with	Heavy-duty steel with	Heavy-duty steel with	Heavy-duty steel with
	angle iron edging	angle iron edging	angle iron edging	angle iron edging
Cover	Fitted tarp	Fitted tarp	Fitted tarp	Fitted tarp
Vibrator	Standard heavy-duty	Standard heavy-duty	Standard heavy-duty	Standard heavy-duty
	12-volt DC	12-volt DC	12-volt DC	12-volt DC
Brake Light	Yes	Yes	Yes	Yes
Work Light	Yes	Yes	Yes	Yes

Metric	11780	11790	11800	11810
Top Screen	Heavy-duty steel with	Heavy-duty steel with	Heavy-duty steel with	Heavy-duty steel with
	angle iron edging	angle iron edging	angle iron edging	angle iron edging
Cover	Fitted tarp	Fitted tarp	Fitted tarp	Fitted tarp
Vibrator	Standard heavy-duty	Standard heavy-duty	Standard heavy-duty	Standard heavy-duty
	12-volt DC	12-volt DC	12-volt DC	12-volt DC
Brake Light	Yes	Yes	Yes	Yes
Work Light	Yes	Yes	Yes	Yes